



bi-alfa cobalt 80 x 1.6 mm, 1.1/1.6 TPI OR bi-alfa cobalt 3" x .063", 1.1/1.6 TPI

CBLT-8016-14H

TOOTH TYPE
N = Normal
H = Hook
P = 16° Positive Rake
X = Triple Chip Grind

KEY	MATERIAL
CBLT	bi-alfa cobalt
MTRX	Matrix2
MSTR	Master
CBRP	bi-alfa cobalt RP
RPMT	bi-alfa RP Master
HMTT	HM-Titan
GRIT	Tungsten Carbide Grit
FLEX	RRR (flexback)
HARD	RRR-Plus (hardback)

KEY	TOOTHING
01	0.75
02	1.25
03	2
04	3
05	4
06	6
07	8
08	10
09	14
10	18
11	24
12	32
13	0.75 / 1.25
14	1.1 / 1.6
15	1.5 / 2
16	2 / 3
17	3 / 4
18	4 / 5
19	4 / 6
20	5 / 6
21	5 / 8
22	6 / 10
23	8 / 12
24	10 / 14

WIDTH	
mm	in
3	1/8
4	5/32
6	1/4
8	5/16
10	3/8
13	1/2
16	5/8
20	3/4
27	1
34	1 1/4
41	1 1/2
54	2
67	2 5/8
80	3

Width & Thickness in millimeters

THICKNESS	
mm	in
0.65	.025
0.80	.032
0.90	.035
1.10	.042
1.30	.050
1.60	.063